



# MODEL 400 SERIES TRAVELING AXLE TRAILER



## Rigid Flat Approach Plate

Plate is fully supported by the four main beams of trailer, allowing the entire trailer bed to become one single, even plane for safe loading from the ground or at dock height.



## Slope Transition

Super-low clearance on the upper deck transition. This makes loading manlifts, forklifts, and other difficult, low-clearance equipment easy to load onto the upper deck.



## Wider Main Beams

Wider Undercarriage.  
Wider Tilt Cylinder Mounts.  
Wider Outer Beam Pivot Point.



## Hydraulic Dock Levels

Each leg is operated independently from the front control panel allowing the operator to raise 62,000 lbs. up to 54" high matching docks, platforms and other trailers.



## Greaseable Pivot Pin

The greaseable pivot-pin is easily accessible from the outside of the trailer for ease of maintenance. All cylinder anchors, hinged kingpin plate and undercarriage rollers have grease zerks. High quality maintenance improves performance for many years of service.



## Tie Downs, Front Roller and Traction Plate

Standard tie downs are combination stake pocket "gotchas" for securement of equipment. The standard slope roller and steel wear plate act as a barrier against rubbing and prevent extra wear on the winch cable. The exclusive Landoll traction plate provides superior grip when loading onto the upper deck.



**Proven Solutions for Your Hauling Needs!**  
**1-800-428-5655 | [www.landoll.com/trailers](http://www.landoll.com/trailers)**



# Standard & Optional Equipment / Features

## Model 425/440/455 Traveling Axle Trailer

S=Standard O=Optional

MODEL 425	25 TON	50,000 lbs.
MODEL 440	40 TON	80,000 lbs.
MODEL 455	55 TON	110,000 lbs.
<b>MAIN FRAME</b>		
- Fabricated 80,000 and 100,000 PSI Yield Beams	S	S S
- Four Beam Design	S	S S
<b>KINGPIN SETTING</b>		
- 21" Setting	S	S S
- 80" Swing Clearance	S	S S
- 2" 5th-Wheel Kingpin Hitch	S	S S
<b>CROSSMEMBERS</b>		
- Alternating 4" and 3" Jr. I-Beam on 9" Centers		S
- Alternating 4" and 3" Jr. I-Beam on 8" Centers		S
- 4" Jr. I-Beam on 8" Centers	S	
<b>WINCH</b>		
- 12,000 lb. Worm Gear with Spring Tension and 85' of ½" Cable	S	S S
- 20,000 lb. Worm Gear with Spring Tension and 85' of ¾" Cable	O	O O
- 30,000 lb. Planetary 2-Speed with 85' of ¾" Flex x 9 Cable	O	O O
<b>DECK AND FEATURES</b>		
- 102" Wide	S	S S
- Deck Rating 40,000 lb. in 16'		S
- Deck Rating 50,000 lb. in 10'		S
- Deck Rating 70,000 lb. in 10'	S	
- 90° Slope Drop	S	S S
- 37" Deck Height (Loaded)	S	S S
- 1⅜" Apitong Hardwood Deck	S	S S
- Aluminum Pullouts to 13' Wide	O	O O
- 7.5° Load Angle		S
- 6.5° Load Angle	S	S
<b>ACCESSORIES</b>		
- Flat Approach Plate with 6 Keyhole Tie Downs	S	S S
- Automatic Slack Adjusters	S	S S
- Main Deck Center Slope Roller	S	S S
- Upper Deck Slope Rollers	O	O O
<b>TIE DOWNS / CHAIN GOTCHAS</b>		
- Double Keyhole Chain Slots with Stake Pockets on 16" Centers	S	S
- Double Keyhole Chain Slots and Stake Pockets on 18" Centers		S

MODEL 425	25 TON	50,000 lbs.
MODEL 440	40 TON	80,000 lbs.
MODEL 455	55 TON	110,000 lbs.
<b>TOOL BOX</b>		
- Twin Side Mounted in Upper Deck with Lockable Doors 7" H x 34" W x 29" D Inside with 6.5" H x 11½" W x 29" D Opening	S	S S
<b>PARKING STANDS</b>		
- Pin Drop	O	O O
- Jost Two Speed Landing Gear	S	S S
<b>SUSPENSION / AXLES</b>		
- Neway Air Ride RLU228 22,500 lb. Capacity	S	S S
- Dock Level Hydraulic 62,000 lb. Capacity (Not Available with 215/75R 17.5 low-pro tires)	O	O O
- Centralized Grease System	S	S S
- (2) 25,000 lb. Axles, Dual Tire, Oil Bath Bearings		S S
- (3) 25,000 lb. Axles, Dual Tire, Oil Bath Bearings	S	
<b>BRAKES</b>		
- 12.25x7.5 Full Air / Spring Brakes ABS, 4S2M	S	S S
<b>TIRES / RIMS</b>		
- 235/75R 17.5 Double Coin Tires	S	S S
- Tire Inflation System	O	O O
- 17.5x6.75 Tubeless Rims	S	S S
<b>HYDRAULIC HOOK UP</b>		
- Hydraulic Quick Couplers / 2,500 PSI - 15GPM	S	S S
<b>LIGHTS</b>		
- Grote "SuperNova" LED 10-Year Warranty, Grote "Ultra Blue Seal" Wiring Harness 7-Year Warranty	S	S S
- Center Mounted Side Turn Signal	S	S S
<b>FINISH / COLOR</b>		
- Steel Grit Shot Blast to Bright Metal	S	S S
- Zinc Rich Primer	S	S S
- TGIC Polyester Powder Coat	S	S S
White, Black, Yellow, Blue, Red, Green		
<b>WEIGHT (ESTIMATED)</b>		
- 425-41' 16,800 lb. +/-3%		S
- 440-48' 17,100 lb. +/-3%		S
- 455-48' 22,800 lb. +/-3%	S	
<b>MORE OPTIONS AVAILABLE INCLUDING WIRELESS REMOTE CONTROL-- CONSULT FACTORY</b>		

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.



**Call 1-800-428-5655**

**Proven Solutions for Your Hauling Needs!**

**[www.landoll.com/trailers](http://www.landoll.com/trailers)**

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

**Remember: Quality is Always a Bargain!**

